

## ToLEDo LYNX D

ToLEDo Lynx D 770LM G24D 840 SL

0030222



### Product features

- LED replacement for compact fluorescent Lynx-D lamps
- 30,000 hours average rated life (L70 F50)
- 3 years warranty
- Quick, simple and safe replacement without rewiring
- Direct retrofit - easiest way to upgrade existing luminaires to LED technology
- Suitable for magnetic ballast/CCG and direct mains 220-240V AC operation
- Low energy consumption and no flickering
- Compact and durable construction
- Minimum and maximum operating temperature: -20°C to 45°C
- Ideal for commercial and residential applications including offices, hotels, restaurants, warehouses, supermarkets, corridors, in addition to living rooms, kitchens and garages
- Warning: ToLEDo Lynx D lamps are not suitable for operation with electronic ballast/ECG operation.



## PRODUCT OVERVIEW

Product name	ToLEDo Lynx D 770LM G24D 840 SL
Technology	LED
Lamp shape	U shape
Type	LED exchangeable
Cap/Base	G24d
Lamp finish	Opal
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
E-number FI	4941327
Warranty	3 years
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	280

## ToLEDo LYNX D

ToLEDo Lynx D 770LM G24D 840 SL

0030222

Photobiological Risk Group	RG0
Wattage (W)	7
Product Voltage (V)	230
Dimmable	No
IP rating	IP20
Product EAN number	5410288302225

### DATA TABLE

#### General data

Product name	ToLEDo Lynx D 770LM G24D 840 SL
Technology	LED
Lamp shape	U shape
Type	LED exchangeable
Cap/Base	G24d
Lamp finish	Opal
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
ETIM Class	EC001959
E-number FI	4941327
Warranty	3 years

#### Optical data

Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	280
Photobiological Risk Group	RG0

#### Electrical data

Wattage (W)	7
Equivalent watt (W)	18
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	5
Inrush Duration (µs)	100
Lamp Energy Label (class)	E

#### Lifetime data

Lifespan L70 B50	30000
------------------	-------

#### Physical data

IP rating	IP20
Nominal Product Length (mm)	145
Nominal Product Width (mm)	34

## ToLEDo LYNX D

ToLEDo Lynx D 770LM G24D 840 SL

0030222

Nominal Product Height (mm)	34
Weight (kg)	0.062


### Packaging

Single packaging type	Carton
Product EAN number	5410288302225
Packaging single length / height (cm)	4.6
Packaging single width (cm)	3.8
Packaging single depth (cm)	15.8
DUN14 (outer)	15410288302222
Units per outer package	6
Packaging outer length / height (cm)	15.0
Packaging outer width (cm)	8.6
Packaging outer depth (cm)	20.4


### Safety data

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Not suitable for household

## PHOTOMETRY



## TECHNICAL DRAWINGS



# SYLVANIA

ToLEDo LYNX D


ToLEDo Lynx D 770LM G24D 840 SL

0030222



SYLVANIA

0030222



**7**  
kWh/1000h



2019/2015

# SYLVANIA


ToLEDo LYNX D

ToLEDo Lynx D 770LM G24D 840 SL

0030222



0030222



**7**  
kWh/1000h



2019/2015